

GP Rechargeable

Takes up to 1970 shots**



**Performance may vary under different operating conditions

Good for All Applications



MP3 Players / CD Players



Digital Cameras



Torches



Toys (Racing Cars)

Environmentally Friendly



Stays Charged longer



Great Savings



AAA



2 x 100AAAHc 1.2V



2 x 85AAAHc 1.2V



2 x 65AAAHc 1.2V



4 x 100AAAHc 1.2V



4 x 85AAAHc 1.2V



4 x 65AAAHc 1.2V

AA (Low Self Discharge)



2 x 270AAHc 1.2V



2 x 250AAHc 1.2V



2 x 210AAHc 1.2V



2 x 180AAHc 1.2V



2 x 130AAHc 1.2V



4 x 270AAHc 1.2V



4 x 250AAHc 1.2V



4 x 210AAHc 1.2V



4 x 180AAHc 1.2V



4 x 130AAHc 1.2V

C



2 x 350CHC 1.2V



2 x 220CH 1.2V

D



2 x 900DHC 1.2V



2 x 700DHC 1.2V



2 x 450DHC 1.2V



2 x 220DH 1.2V

9V



1 x 17R8H 8.4V



Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge) (mAh)		Nominal Dimension (mm)		Weight (g)	Standard Charge		1 Hr Charge Current (mA)#
			Minimum	Typical	Diameter	Height		Current (mA)	Time (Hour)	

NICKEL METAL HYDRIDE SERIES

AA	GP270AAHC**	1.2	2550	2600	14.5	50.5	31.5	255	16	2550
	GP250AAHC**	1.2	2450	2450	14.5	50.5	31.0	245	16	2450
	GP210AAHC**	1.2	2000	2050	14.5	50.5	28.0	200	16	2000
	GP180AAHC**	1.2	1800	1850	14.5	50.5	28.0	180	16	1800
	GP130AAHC**	1.2	1300	1340	14.5	50.5	25.0	130	16	1300
AAA	GP100AAAHC	1.2	930	970	10.5	44.5	15.2	93	16	930
	GP85AAAHC	1.2	850	870	10.5	44.5	14.2	85	16	850
	GP65AAAHC**	1.2	650	680	10.5	44.5	13.0	65	16	650
C	GP350CHC	1.2	3500	3500	26.2	50.0	78.5	350	16	Not Applicable
	GP220CH	1.2	2200	2200	26.2	50.0	61.0	220	16	Not Applicable
D	GP900DHC	1.2	9000	9000	34.2	61.5	173.0	900	16	Not Applicable
	GP700DHC	1.2	7000	7000	34.2	61.5	155.0	700	16	Not Applicable
	GP450DHC	1.2	4500	4500	34.2	61.5	130.0	450	16	Not Applicable
	GP220DH	1.2	2200	2200	34.2	61.5	71.0	220	16	Not Applicable
9V	GP17R8H**	8.4	170	175	15.7(T)X26.5(W)X48.5(H)		32.0	17	16	170


One hour rate with charge termination control. * After charging at 0.1 C for 16 hours. ** With UL approval.



GP ReCyko+

Pre-charged rechargeable battery

Stays charged longer!



* Capacity related subject to full charge & storage conditions
** Applicable to AA & AAA

Great Savings

Can be recharged and reused up to 1,000 times.



Environmentally Friendly

GP ReCyko+ contributes to the environment through greatly reducing battery disposal, answering modern customer's demand for more environmentally friendly goods.



Complies with IEC standard

Good for All Applications



MP3 Players / CD Players



Digital Cameras



Torches



Toys (Racing Cars)

AA

AAA



2 x 210AAHCB 1.2V



4 x 210AAHCB 1.2V



2 x 85AAAHC B 1.2V



4 x 85AAAHC B 1.2V

C

D



2 x 300CHCB 1.2V



2 x 260CHB 1.2V



2 x 570DHCB 1.2V



2 x 260DHB 1.2V

9V



1 x 15R8HB 8.4V



GP ReCyko+ SERIES

Cell Size	Model No.	Nominal Voltage (V)	Capacity (0.2C discharge) ⁽¹⁾ (mAh)		Nominal Dimension (mm)		Weight (g)	Standard Charge		1 Hr Charge Current (mA) [#]
			Minimum	Typical	Diameter	Height		Current (mA)	Time (Hour)	
AA	GP210AAHCB**	1.2	2000	2050	14.5	50.5	30	200	16	2000
AAA	GP85AAAHC B**	1.2	800	820	10.5	44.5	14	80	16	800
C	GP260CHB	1.2	2600	2600	26.2	50.0	62	260	16	2600
	GP300CHCB	1.2	3000	3000	26.2	50.0	70	300	16	3000
D	GP260DHB	1.2	2600	2600	34.2	61.5	72	260	16	2600
	GP570DHCB	1.2	5700	5700	34.2	61.5	124	570	16	5700
9V	GP15R8HB	8.4	150	155	15.7(T)X26.5(W)X48.5(H)		32	15	16	150

[#] One hour rate with charge termination control ⁽¹⁾ After charging at 0.1 C for 16 hours ^{**} With UL approval